Sisecam Flat Glass Italy S.R.L., Via J. Linussio, 2
33058 San Giorgio di Nogaro (UD) - Italy

DECLARATION OF PERFORMANCE

No: DFCH331PN

SISECAM LAMINATED GLASS 33/1

composition: 3/0,38/3
EN 14449:2005/AC:2005
Notified Body:1694
Laminated glass and laminated safety glass for use in buildings and construction works

Performance:

	AVPC System	Performance
Resistance to fire (EN 13501-2)		NPD
Reaction to fire (EN 13501-1)		NPD
External fire performances (EN 13501-5)		NPD
Bullet resistance (EN 1063)		NPD
Explosion resistance (EN 13541)		NPD
Burglar resistance (EN 356)		NPD
Pendulum body impact resistance (EN 12600)		2(B)2
Resistance against sudden temperatures changes and temperature differentials		40 K
Wind, snow, permanent and imposed load resistance		45/45
Direct airborne sound insulation (EN 12758)		NPD
Thermal properties (EN 673)		5,7 W/m^2K
Radiation properties (EN 410): - Light transmission and reflection - Solar transmission and reflection		 89% 8% 75% 7%
Durability		PASS
Emissivity		0,84

NPD: performance not determined

The performance of the product complies with the above stated performance
This declaration of performance is issued under the responsibility of the manufacturer
Signed for and on behalf of the manufacturer

San Giorgio di Nogaro, 01/01/2020

Beytullah Sahin
General Manager